



Better tile/stone glue

- High adhesion.
- Wall covering for all absorbent and low-absorbent tiles such as granite, porcelain, and marble up to 60x60cm in size.
- Alternative to traditional mortar.
- In compliance with **GREENGUARDS, Low VOCs** standard - safe for users' health.

Ingredients: Sand, cement, and other additives.

Application: Suitable for absorbent and low-absorbent tiles such as ceramic, granite, porcelain, and marble, with sizes up to 60x60cm for interior areas such as living rooms, bedrooms, offices,....

Suitable for cement walls and floors of exterior areas under the roof.

SPECIFICATION AND PRESERVATION

Packing: 40kg/unit

Colours: Grey

Shelf life and storage: Within 1 year from date of manufacture in unopened packaging and stored in a dry, well-ventilated area. If the package has been opened, it should be stored tightly closed and in a dry, ventilated area and should be inspected prior to use.

SPECIFICATIONS

Items	webertai A500
Norm*	1.4 kg/m ² /mm
Specific weight	~1.4 g/cm ³
Time for the chemical ingredients to take full effect	≤ 3- 4 mins
Time for mixing and use	4 hours
Visualized Open time	≥ 15 mins
Adjusting time	10 mins
Waiting time before grouting	24 hours
Thickness	2- 10 mm

QUALITY CERTIFICATION

	Standard	webertai A500	Test method
Tensile adhesion strength after 28 days	≥ 0.5 (N/mm ²)	Pass	ISO 13007-2 part 4.4.4.2 and EN 1348-8.2
Tensile adhesion strength after water immersion after 28 days	≥ 0.5 (N/mm ²)	Pass	ISO 13007-2 part 4.4.4.3 and EN 1348-8.3
Open time		~ 20 mins	TCVN 7899-2/ ISO 13007-2 part 4.1 and EN 1346

*Norm for reference only: 1.4kg/m² for 1mm thickness (minimum thickness 3mm)
The actual rate depends on the substrate surface, tile size and workmanship.

SUBSTRATE PREPARATION

SURFACE PREPARATION

1

Surface must be flat, hard, clean, not stagnant, not too dry.

PREPARE TILE

2

Do not soak bricks in water. Make sure the tile is dry and clean before gluing.

PREPARE TOOLS

3

Weber serrated trowel.

PRODUCT PREPARATION

4

1 water + 4 glue

Put the water in the bucket first and the webertai A500 glue slowly in the back **by weight**: 1 water and 4 glue (rate 25%). Mix well until the mixture is smooth and uniform. Wait 3-4 minutes for the chemical ingredients to take effect.

CONSTRUCTION METHOD

1

Apply glue on the surface of the wall/floor to be tiling, then use a serrated trowel, hold the trowel at about 60° to pull the glue evenly to the surface.

2

In case the tile size is up to 25x25cm, it is necessary to apply a thin layer of glue on the back of the tile.

3

Use a rubber hammer to knock evenly on the surface of the brick

4

24h waiting time

Use a damp sponge to clean excess glue and wait 24 hours for the glue to dry before grouting/tightening

5

Scrubbing/grouting with Weber rubber trowel. Wait 24 hours before traffic.

APPLICATION NOTE FOR TILE/STONE

- For large stones, it is recommended to spread a thin layer of webertai A500 glue on the back of the stone to ensure that the glue and stone are well bonded, increasing adhesion.
- Do not apply glue in patches behind the tile. This way of plastering will create a space under the tile and cause cracking, water infiltration and peeling later.
- The glue mixture should be used up within the specified time. Avoid using glue on overheated substrates and limit direct sunlight.

HEALTH SAFETY INFORMATION

- The composition contains cement, so it can cause allergies when in contact. Contact with wet grout can cause dermatitis, burning or irritation. Similarly, in cases when the body produces too much fluid (e.g. sweating or watery eyes) there is also a case of dermatitis, burning or burning.
- Avoid direct contact with skin or eyes. Limit dust flying and avoid breathing dust directly during construction.
- In case of contact with the body, wash with plenty of clean water.
- Should wear gloves and glasses when working.
- Keep out of reach of children .

Product recommendation

For cases of	Tiling interior walls of more than 8m high	Ceramic and stone tiling to prevent tarnishing or yellow stains	Tiling over existing tiles or existing painted surfaces	Tiling over fiber cement boards or wooden surface	Tiling over gypsum board	Tiling over metal or plastic surfaces
Recommended products	webertai A1000 tile adhesive	webertai no-stain tile adhesive	webertai A800 webertai A600 webertai A1000 tile adhesive	weberprim 2 (as primer) and webertai A1000 tile adhesive	webertai A1000 tile adhesive	weberpox easy tile adhesive and grout

Disclaimer:

The information related to Weber products is provided and recommended based on our knowledge and experience under proper storage, testing, and use conditions. In actual application, due to differences in materials, aggregates, and actual site conditions, we cannot guarantee any particular purposes of the product, or any liability for the information, recommendations, or advice from our part. Users need to consult the latest documentation provided as well as check the suitability of the product for the desired application purpose.